



Nr. / No.	Länge / Length (m)
95736	0.15
95735	0.30
93922	0.60
93918	1.00
93181	1.80
93920	3.00
93921	5.00

Micro-USB Daten- und Ladekabel

- Verbinder: USB-A Stecker > Micro USB-B St.
- Innenleiter: AWG28 (4 x 7/0.12mm) Kupfer
- Isolierung: PVC; schwarz
- Schirmung: doppelt; 1mm AL-Folie + (44/0.12mm) Geflecht
- USB Standard: High Speed USB 2.0
- Datenrate: max. 480Mbit/s
- RoHS-konform

Micro USB data and charging cable

- USB-A plug > Micro USB-B plug
- Inner conductor: AWG28 (4 x 7/0.12mm) copper
- Insulation: PVC; black
- Shielding: double; 1mm AL foil + (44/0.12) Braiding
- USB Standard: High Speed USB 2.0
- Data rate: max. 480Mbps
- RoHS compliant

Änderungen

Datum	Name	gez.:	Datum	Name
17.02.2015	tf	gez.:	30.07.2014	tf
		gepr.:	30.07.2014	tf
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung

USB MICRO-B SCHWARZ



Blatt

Zeichnungs-Nr.:

V2

von